## JC151AP





LCD Panel	Display size	15" (38,1 cm)
	Panel Type	TN, Active Matrix
	Brightness	250 cd/m <sup>2</sup>
	Contrast	600:1 (typ.)
	Pixel pitch	0,297 x 0,297 mm
	Resolution (H x V)	1024 x 768 (XGA)
	Response time	12 ms
	View angles LR,UD	130° / 100°
	Display colors	16,2 Mio.
	Color	9300K, 6500K, User
		Mode
	Display Surface	AG
Input	Input 1	D-Sub x 1, Audio x 1
	Input 2	
	Input 3	
Output	Output 1	
	Output 2	
	Headphone	
	Speakers	1W x 2
Power	Supply	AC 100~240V,
	- Laber.)	50~60Hz, internal
	Consumption	30 W
Operating Condition	Temperature	0 - 40°C
	Humidity	0 - 90%
Physical	Dimension (W*D*H)	340 x 153 x 395 mm
	Packing dimension (W*D*H)	395 x 130 x 395 mm
	Net weight	3,75 kg
	Gross weight	4,1 kg
	Tilt	-3° - 20°
	Kensington Lock	<u> </u>
	VESA mounting	100 mm
Controls	Front control	Menu, +, - , Select,
		LED/Power
	On screen display	EN, SC, TC, DE, FR, IT,
		ES, JS, DU
Certification	Safety	CE, FCC, BSMI,
	· · · · ·	UL/CUL, TUV/GS, CCC
		, ,
	Emission	TCO99
	Power saving	
Extras 1		
Extras 2		
Extras 3		
Accessories		Powercord, VGA-Cable,
		Audio-Cable, QSG,
		Manual (CD)
		IVICALIMENT USALAT

Specifications are subject to change without notice. Error accepted.

HANNspree Europe GmbH Siemensring 66 47877 Willich GERMANY

Tel: +49 (0)2154/95 323-0 Fax: +49 (0)2154/95 323-123 http://www.hannsg.com info.europe@hannspree.com

